Locations Germany - Technical Data

Hot-Dip Galvanizing

Location	Company	Kettle Dimensions* (Length/Width/Height) Small Parts Basket Size Ø x H (mm) *Usable kettle dims. vary by component size	ZINQ Management System certified acc. to				Hot-Dip Galvanizing to Standard		Additional Approvals
			DIN EN ISO 9001:2015 DNV	DIN EN ISO 14001:2015 DNV	DIN EN ISO 50001:2018 DNV	Cradle to Cradle® Certified	DIN EN ISO 1461:2022	DASt-Richtlinie 022:2016	DIN EN 1090:2009 by the IFO Institute
Alsdorf	ZINQ Alsdorf GmbH	7,00 x 1,50 x 3,20 m	•	•	•	•	•	•	•
Arnsberg	Feuerverzinkerei Picker GmbH & Co. KG	6,70 x 1,50 x 2,70 m	• d. TÜV NORD	• d. TÜV NORD	• d. TÜV NORD		•	•	•
Beilstein	ZINQ Beilstein GmbH & Co. KG	7,00 x 1,50 x 3,00 m	•	•	•	•	•	•	•
Bruchsal	ZINQ Bruchsal GmbH & Co. KG	7,00 x 1,50 x 3,00 m	•	•	•	•	•	•	•
Castrop-Rauxel	ZINQ Castrop-Rauxel GmbH & Co. KG	7,50 x 2,20 x 3,50 m	•	•	•	•	•	•	•
Dresden	ZINQ Dresden GmbH	7,50 x 1,50 x 3,10 m	•	•	•	•	•	•	•
Duisburg	ZINQ Duisburg GmbH & Co. KG	7,00 x 2,00 x 3,00 m	•	•	•	•	•	•	•
Essen	ZINQ Essen GmbH	7,00 x 1,50 x 3,20 m	•	•	•	•	•	•	•
Frankfurt (Oder)	ZINQ Frankfurt (Oder) GmbH	7,00 x 1,20 x 3,50 m	•	•	•	•	•	•	•
Gelsenkirchen	ZINQ Gelsenkirchen GmbH & Co. KG	17,20 x 1,80 x 3,20 m	•	•	•	•	•	•	•
Hagen microZINQ®-Anlage	ZINQ Hagen GmbH & Co. KG	7,00 x 1,80 x 3,20 m	•	•	•	•	Galvanizing per Standard 50997	General Building Approval (AbZ)	
Heldrungen	ZINQ Heldrungen GmbH	7,00 x 1,30 x 2,80 m	•	•	•	•	•	•	•
Kissing b. Augsburg	ZINQ Kissing/Augsburg GmbH	Vertical galvanizing: Parts up to 7.20 m	•	•	•	•	•	•	•
Landsberg	ZINQ Landsberg/Halle GmbH	15,50 x 2,00 x 3,00 m	•	•	•	•	•	•	•
Lausitz	ZINQ Lausitz GmbH & Co. KG	6,50 x 1,40 x 3,60 m 440 x 280 mm	•	•	•	•	•	•	•
Leipzig	ZINQ Leipzig GmbH	7,00 x 1,50 x 3,00 m	•	•	•	•	•	•	•
Maintal	ZINQ Beilstein GmbH & Co. KG Betriebsstätte Maintal	8,50 x 2,60 x 3,30 m 460 x 600 mm	•	•	•	•	•	•	•
Netzschkau	ZINQ Netzschkau GmbH	17,20 x 1,50 x 3,20 m	•	•	•	•	•	•	•
Rheine-Hauenhorst	Verzinkerei Rheine-Hauenhorst GmbH & Co. KG	7,00 x 1,50 x 2,70 m					•	•	
Trebbin	Verzinkerei Trebbin GmbH	7,50 x 1,50 x 2,80 m	•				•	•	•

Locations Germany - Technical Data

Powder Coating

Location	Company	Max. Part Dimensions (Length/Height/Depth)	Max. Unit Weight	ZINQ Management System certified acc. to		Certified per DIN EN ISO 9001:2015 DNV	Certified acc. to DIN EN 1090:2009 by the IFO Institute
				DIN EN ISO 14001:2015 DNV	DIN EN ISO 50001:2018 DNV		
Bruchsal	COATINQ Bruchsal GmbH & Co. KG	8,00 x 2,50 x 0,85 m	1,2 t	•	•	•	•
Castrop-Rauxel	COATINQ Castrop-Rauxel GmbH	8,60 x 2,60 x 0,60 m	1 t	•	•	•	•
Leipzig	ZINQ Leipzig GmbH	8,00 x 2,50 x 1,00 m	1,3 t	•	•	•	•

Locations Benelux - Technical Data

Hot-Dip Galvanizing

Location	Company	Kettle Dimensions* (Length/Width/Height) *Usable kettle dims. vary by component size	ZINQ Management System certified acc. to				Hot-Dip Galvanizing to Standard		Additional Approvals
			EN ISO 9001:2015	EN ISO 14001:2015	EN ISO 50001:2018	Cradle to Cradle® Certified	EN ISO 1461:2022	DASt-Richtlinie 022:2016	EN 1090:2009 by the IFO Institute
Antwerpen	ZINQ Antwerpen	19,00 x 1,90 x 3,30 m	•	•	•	•	•	•	•
Charleroi	ZINQ Charleroi	7,50 x 2,00 x 3,30 m	•	•	•	•	•		•
Gent	ZINQ Gent	15,50 x 1,60 x 2,95 m	•	•	•	•	•		•
Houthalen	ZINQ Houthalen	9,50 x 2,60 x 3,30 m	•	•	•	•	•	•	•
Ieper	ZINQ Ieper	7,50 x 1,50 x 2,70 m	•	•	•	•	•		•
Pelt	ZINQ Pelt	9,00 x 2,15 x 3,30 m	•	•	•	•	•	•	•
Veenoord	ZINQ Veenoord	8,50 x 2,20 x 3,25 m	•	•	•	•	•	•	•
Kruisem	ZINQ Kruisem	6,50 x 1,50 x 3,50 m	•			•			

*DASt-Richtlinie 022: ZINQ Gent, ZINQ Charleroi and ZINQ Ypern; in co-production with ZINQ Antwerpen

Locations Benelux - Technical Data

Powder Coating

Location	Company	Max. Part Dimensions (Length/Height/Depth)	Max. Unit Weight	Certified for coat-ing HDG steel per DIN 55633:2021	Certified per EN ISO 9001:2015	Certified per EN 1090:2009 by the IFO Institute	Certified per EN ISO 14001:2015
Nieuw Amsterdam	ZINQ Poedercoating	Linie 1: 6,00 x 0,50 x 2,50 m Linie 2: 9,00 x 3,00 x 2,80 m	0,275 t 1,5 t	•	•	•	•
Mouscron	ZINQ Mouscron	Linie 1: 7,00 x 2,75 x 3,25 m Linie 2: 15,00 x 0,90 x 3,00 m	1,5 t				

Locations Poland - Technical Data

Hot-Dip Galvanizing

Location	Company	Kettle Dimensions* (Length/Width/Height) *Usable kettle dims. vary by component size	ZINQ Management System certified acc. to				Hot-Dip Galvanizing to Standard		Additional Approvals
			PN EN ISO 9001:2015	PN EN ISO 14001:2015	PN EN ISO 50001:2018	Cradle to Cradle® Certified	PN EN ISO 1461:2022	DASt-Richtlinie 022:2016	EN 1090:2009 by the IFO Institute
Bydgoszcz	Metalcynk Sp. z o.o.	1,85 x 1,70 x 2,80 m	•				•	•	•
Ruda Śląska	Ocynkownia Pokój Sp. z o.o.	7,30 x 1,50 x 2,70 m	•				•		

Locations Poland - Technical Data

Powder Coating

Location	Company	Max. Part Dimensions (Length/Height/Depth)	Certified
Ruda Śląska	Ocynkownia Pokój Sp. z o.o.	8,00 x 1,60 x 2,00 m	PN-EN 13438

Locations France - Technical Data

Hot-Dip Galvanizing

Location	Company	Kettle Dimensions* (Length/Width/Height) *Kesselnutzmaße weichen je nach Bauteildimension ab.	ZINQ Management System certified acc. to					Hot-Dip Galvanizing to Standard	
			EN ISO 9001:2015	EN ISO 14001:2015	EN ISO 45001:2018	EN ISO 50001:2018	Cradle to Cradle® Certified	NF EN ISO 1461:2022	DASt-Richtlinie 022:2016
Saint Pourçain sur Sioule	ZINQ Auvergne	16,00 x 2,00 x 3,20 m	•	•	•	•	•	•	
Chabeuil	ZINQ Valence	13,00 x 1,60 x 2,80 m	•	•	•		•	•	
Escrennes	ZINQ Val de Loire	Linie 1: 8,00 x 1,80 x 2,90 m Linie 2: 5,00 x 1,40 x 2,20 m Linie 3: 3,00 x 1,40 x 2,00 m Linie 4: 0,60 x 0,20 x 0,20 m	•	•	•		•	•	
Vivier au court	ZINQ Ardennes	Linie 1: 4,40 x 1,40 x 2,10 m Linie 2: 0,60 x 0,20 x 0,20 m	•	•	•		•	•	
Senozan	ZINQ Mâcon	6,30 x 1,50 x 3,00 m	•	•	•		•	•	
Meyzieu	ZINQ Lyon	7,50 x 1,30 x 2,30 m	•	•	•		•	•	
Canejan	ZINQ Bordeaux	7,40 x 1,25 x 2,20 m	•	•	•		•	•	
Saint-Symphorien-des-Bruyères	ZINQ Normandie	5,00 x 1,30 x 3,00 m	•	•	•		•	•	
Carquefou	ZINQ Nantes	15,80 x 2,22 x 2,80 m	•	•	•		•	•	•
Hénin-Beaumont	ZINQ Artois	12,80 x 1,80 x 2,80 m	•	•	•		•	•	
Honnechy	ZINQ Cambrésis	15,30 x 1,70 x 2,60 m	•	•	•		•	•	

Locations France – Technical Data

Powder Coating

Location	Company	Max. Part Dimensions (Length/Height/Depth)	Max. Unit Weight	Certified for coating HDG steel per DIN 55633:2021		
				EN ISO 9001:2015 DNV	EN ISO 14001:2015 DNV	EN ISO 45001:2018 DNV
Saint Pourçain sur Sioule	COATINQ Auvergne	Blasting: 20,00 x 4,00 x 4,00 m Metal spraying: 20,00 x 4,00 x 4,00 m Automatic: 16,00 x 2,50 x 1,10 m Manual: 17,00 x 2,60 x 2,50 m	15 t 15 t 2 t 15 t	•	•	•
Vivier au Court	COATINQ Ardennes	Standard: 8,50 x 2,50 x 2,70 m After evaluation: 9,00 x 2,50 x 3,00 m	1,8 t	•	•	•
Bernay	COATINQ Normandie Bernay	8,00 x 3,00 x 3,00 m	1,5 t	•	•	
Breteuil sur Iton	COATINQ Normandie Breteuil	Automatic: 1,50 x 3,00 x 0,90 m Manual: 1,20 x 2,20 x 0,60 m	80 kg	•	•	
Carquefou	ZINQ Nantes	Liquid paint: 1,50 x 3,00 x 0,90 m Powder coating: 1,20 x 2,20 x 0,60 m	3,5 t 0,6 t	•	•	•